

START SAFETY

+1 (800) 671 9662



We use 3M
Retroreflective
Sheeting.



ANCHOR[®] MAST[®] TYPE III BARRICADE



ANCHOR[®] MAST[®] FEATURES:

Anchor Mast Type III Barricade consists of Anchor Mast Upright, Anchor Base, and Wave Centerboard.

The unit is manufactured from high-density polyethylene plastic with UV stabilizers.

Mast Upright features molded-in warning light mounts for Type A and C warning lights. Mounting holes hold two flags, front and back.

Mast Upright's molded through-holes add strength and support.

Wave Centerboards are available in 4', 6', and 8' lengths. Retro-reflective sheeting is available in Engineer, Hi-Intensity, and Diamond Grade sheeting. Retro-reflective sheeting meets all state and federal specifications. Wave boards accepts sheeting on both sides.

Anchor Base is available in two lengths — 48" & 60".

Patents: <http://bit.ly/3cHVTp8>



MAST[®] UPRIGHT FEATURES:

Molded through-holes are recessed for flush-mounted hardware which protects sheeting. Raised Centerboard Locators make installation of Wave Centerboards easier and faster.

LIGHT AND FLAG MOUNT FEATURES:

Light and flag mount (LFM) accessory, sold separately, attaches to perforated stainless steel tube (PSST) uprights. Accepts one or two flags and one warning light. Manufactured from high-density polyethylene plastic with UV stabilizers. PSS does not offer PSST uprights for sale.

ANCHOR[®] BASE FEATURES:

Available in two styles: for plastic uprights or PSST uprights. Anchor Base for plastic uprights features a 4" x 4" mount. Anchor Base for PSST uprights features a 1 3/4" x 1 3/4" mount. "Press-fit" installation means no tools required to attach uprights. Includes molded-in carrying handle.

Features molded in fill-hole and cap to fill with sand. Anchor 48" holds 45 lbs, Anchor 60" holds 60 lbs. Rubber anti-skid pad on bottom helps increase traction and decrease movement.

We are a proud member of:



Innovations for Safety[®]



PSS | 2444 Baldwin Road, Cleveland, OH 44104 | 800.662.6338 | PSS-Innovations.com

5/21