

# START SAFETY

# +1 (800) 671 9662

**3M** We use 3M Reflective Sheeting.



## RightPath SAFETYRAIL Pedestrian Barricade



### SAFETYRAIL™ FEATURES:

SafetyRail is a continuous, interlocking device designed for creating accessible work zones. This device adheres to ADA guidelines and MUTCD 2009 Edition Standards as a sidewalk closure barricade and longitudinal channelizer.

SafetyRail is designed for use with PSS Wave® Guide Rail. The upper Wave Guide Rail is smooth, continuous, and safe for trailing of the hand. The lower Wave Guide Rail measures 1.5" from the ground, reducing potential for trapped cane tips. Wave "notch" design keeps guide rails securely in bushings.

*US Patents Nos. 8,302,937; 7,536,973 B2.*



### SAFETYRAIL FEATURES:

**Dimensions:** 3.25" W x 38" H x 24" L at base

**Weight:** 7 lbs empty or up to 25 lbs with sand

**Material:** High-density polyethylene plastic, UV inhibitors

**MASH Eligibility:** SafetyRail: WZ-359

**Wave Guide Rail:** 0.8" x 7.5" x 48" or 72"  
High-density polyethylene plastic, UV inhibitors

### PSS WAVE GUIDE RAIL:

Available in four-foot or six-foot lengths. Encapsulated ends eliminate cane or hand snagging hazards.

Retroreflective sheeting meets all state and federal specifications and is available in Engineer, Hi-Intensity, and Diamond grades. Wave accepts sheeting on one or both sides.

We are a proud member of:

