




<b>MODULE SIZE</b>	<b>ACTUAL</b> 7.5' L x 14' W x 4" H (105 ft <sup>2</sup> ) 2.3 m x 4.3 m x 10.16 cm (9.75 m <sup>2</sup> )  <b>USABLE (DUE TO FLANGE)</b> 6.5' L x 13' W x 4" H (84.5 ft <sup>2</sup> ) 1.981 m x 3.962 m x 10.16 cm (7.85 m <sup>2</sup> )
<b>WEIGHT</b>	1,095 lbs (496.7 kg)
<b>FLANGE THICKNESS</b>	2 in (5.08 cm)
<b>COLOR</b>	Beige (Custom colors available)
<b>MATERIAL</b>	High-Density Polyethylene (HDPE) with special impact modifiers that incorporate UV resistance and anti-static properties
<b>WEIGHT LOADING</b>	600 psi, depending on subsurface conditions
<b>FLAMMABILITY RESISTANCE</b>	UL94HB
<b>CONNECTION SYSTEM</b>	Proprietary, self-aligning, aluminum cam S <sup>2</sup> Lock™ system that connects the overlapping flange from adjacent mats with a simple twist of a standard T-bar
<b>SHIPPING INFO</b>	U.S. standard 48 ft. flatbed truck: 40 mats 40 ft ISO shipping container: 40 mats 20 ft ISO shipping container: 20 mats – 1 stack, 20 full mats high U.K. lorry/EU trucks: Up to 50 mats