



<b>MODULE SIZE</b>	<b>ACTUAL</b> 6.8' L x 10' W x 2.5" H (68 ft <sup>2</sup> ) 2 m x 3 m x 6.4 cm (6 m <sup>2</sup> ) <b>USABLE PLATFORM</b> 6' L x 9.3' W x 2.5" H (55.8 ft <sup>2</sup> ) 1.9 m x 2.8 m x 6.4 cm (5.3 m <sup>2</sup> )
<b>WEIGHT</b>	496 lbs 225 kg
<b>COLOR</b>	Beige
<b>MATERIAL</b>	High-Density Polyethylene (HDPE) with special impact modifiers that incorporate UV resistance and anti-static properties
<b>WEIGHT LOADING</b>	400 psi, depending on subsurface conditions
<b>FLAMMABILITY RESISTANCE</b>	UL94HB
<b>CONNECTION SYSTEM</b>	Proprietary, self-aligning, composite cam lock system connects the overlapping flange from adjacent mats with a simple twist of a standard hex key
<b>SHIPPING INFO</b>	U.S. standard 48 ft. flatbed truck: 90 mats 40ft ISO shipping container: 90 mats 20ft ISO shipping container: 45 mats U.K. lorry/EU trucks: Up to 120 mats

3ASR 200605 ©2020 Signature Systems



[startsafety.com](http://startsafety.com)