

V-Fence

Description:

The V-Fence provides an alternative solution to traditional metal fencing. At 2m in height, the long-lasting, non-conductive panel can be easily installed by one person and is safe to handle with no sharp edges. No mesh that could separate reduces potential injuries to the workforce or general public. Complete with Chapter 8 conforming reflective panel and pre-manufactured fixing holes to attach permit/courtesy signs when required.

Features:

- Completely non-conductive – no risk of shock
- Single person lift and installation
- No metal mesh reducing potential injuries and workload for workforce and public
- Safe stacking – 40 per pallet
- Highly reflective panel
- Complete angular movement to navigate bends and corners
- Compatible with both Multifit blocks and WonderWall Base
- 100% recyclable.
- Available in corporate colours and branded to suit*



Linear Run



Anti-trip



Centre Holes

Standards:

- Reflectivity requirements of **BSEN12899-1**
- Chapter 8 - The Traffic Signs Manual
- Traffic Signs Regulations & General Directions

Height:	2005 mm (78.94 inches)
Overall Width:	1100 mm (43.3 inches)
Fence Width:	1000 mm (39.37 inches)
Depth:	75 mm (2.95 inches)
Stacking Depth:	50 mm (1.97 inches)
Weight:	8.20 kg (18 pounds)

*Min. Order Quantity Applies
*All weights are approximate



The information given on these sheets is typical of the product depicted it must not be interpreted as a guarantee of individual product performance and/or characteristics. We reserve the right to alter specifications and designs without prior notice. All measurements are in millimetres (mm)



FM 673547