

WonderWall™

Description:

The WonderWall™ is a heavy duty, enhanced Barrier system. The robust Barrier gives stability in high winds without the need for extra ballast. It creates a safer working environment when deployed near the road side or excavations on site. Can be moved with ease by one person, and can be moved via Fork-lift truck when the Bases are stacked.

Features:

- Pedestrian & Plant WonderDoor™ can be used.
- The WonderDoor™ system can be created using the Melba Swintex S-Clip, as well as connection to existing Barrier systems.
- A separately moulded peg that is securely fixed allows a quick & easy connection to the next Barrier.
- Embossing with corporate branding on both the Base and Top.
- Tops and Bases can be coloured coded for corporate identity .
- Holes in base for Fork lift entry.
- Location holes for a 23.62"x 17.71" (600 x 450) Courtesy Sign, & Lamp bracket.
- Bases can stack with one another.
- Compatible with existing systems.
- Facility to take a double decked system.
- 21 pieces each to a pallet.



Connection



Stacking



Embossing



Standards:

- Reflectivity requirements of **BSEN12899-1**
- Chapter 8 - The Traffic Signs Manual
- Traffic Signs Regulations & General Directions

Height:	39.37 inches (1000mm)
Width:	44.88 inches (1140mm)
Barrier Depth:	1.97 inches (50mm)
Base Depth:	19.69 inches (500mm)
Weight:	47.95 lbs (21.75kg)

The information given on these sheets is typical of the product depicted it must not be interpreted as a guarantee of individual product performance and/or characteristics. We reserve the right to alter specifications and designs without prior notice.